

The AiroPower System

Not just a replacement to your hydraulic body kit - it's much more!

AiroPower is an air operated pneumatic push and pull body repair system. Quick and easy to operate with 5.25 tons of power in one tool!

Compact and light, ideal for single person operation and oil free, avoiding the risk of damage to car interiors.



5.25
TONS OF PRESSURE 



**REQUEST
A DEMO**

Call to arrange
a visit from our
sales team

Scan Me



**YOUTUBE
VIDEO**



AIROPOWER BENEFITS

- ✓ Quick and easy operation - connect the air supply and just pull the lever
- ✓ High Power - push and pull capacity of up to a max of 5.25 tons (8 bar)
- ✓ No hydraulics - clean to use with no oil leaking from cylinder or coupling and damaging car interior
- ✓ One body for pushing and pulling - simply reverse the valve
- ✓ Remote control for safety - safe working distance of up to 2 metres
- ✓ Small size - use in narrow spaces like a conventional mini-ram

THE COMPLETE PROFESSIONAL SYSTEM



With extra accessories wheel arches are easily pushed out

A Cost-Effective Solution

These days many body re-alignment jobs do not warrant mounting on the jig. Yet they are complex repairs requiring to be pulled back to shape. The AiroPower System offers a low cost solution giving the repairer the ability to make decent money out of this type of work.

AiroPower is a hand held alignment tool with 5.25 tons of push and pull power. Being air powered means that the unit is compact, lightweight (only 3.7kg) and clean to use. It comes with a remote control for safety giving instant, fingertip control. It's easy to set up and comes with a comprehensive range of accessories.



Typical applications:

Door Aperture Re-alignment

Set up with extension tubes and rubber faced pushing heads or clamps and push opposite pillars from corner to corner, top to bottom or side to side.

Damage to the rear or side of the vehicle can be quickly repaired using a combination of push and pull action. Using a set-up of three extension tubes and clamps, two clamps are arranged either side of the damage, whilst the other is clamped to the damaged area. Activating the tool sees the undamaged area fixed whilst the damage is pulled out.

Wheel Arch Repair

This set-up uses a short tube, flat foot and V attachment. Whilst the damage is under tension, repair work can be carried out utilising the delicate control and versatility of the tool. AiroPower has applications in the bodyshop and auto racetrack. It replaces the need to anchor vehicle in any repair procedure.