

YANMAR

GS-PG6DY3000



Super silenced generator equipped with Yanmar 3000 RPM engine. Designed for automatic starting via a convenient connector on the instrument panel. Equipped with central liftin hook and forkable base, trolley available for practical handling

Auto engine protection shutdown system with warning lights for: battery charger failure, low fuel level, low oil pressure

1 x 32A 230V single phase socket

1 x 16A 230V single phase socket

Starting battery

Emergency stop button

Hourmeter

Power output protections

Earth leakage circuit breaker (ELCB)

Connector for AMF-ATS panel and/or remote control

Central lifting hook

Fork-lift pockets

Noise Level (LWA)	90 (65dB a 7m)
AC Generator 50Hz	Synchronous
Single Phase Max. Power	6kVA - 230V
Power Factor	Cos ϕ 0.8
Yanmar Engine	L100V
Fuel	Diesel
No. Cylinders	1
Power	8.8HP (6.5kWm)
Displacement	1123cm ³
Cooling System	Air
Starting System	Electric
Fuel Tank Capacity	30l
Fuel Consumption @ 75%	2.2l/h
Insulation Class	H
Ambient Temperature	40°C
Altitude	1000m
Degree of Protection	IP23
Dimensions (LxWxH)	1160 x 631 x 872mm
Dry Weight	200Kg

OPTIONAL ACCESSORIES

PETRO CHEMICAL SPECIFICATIONS

