

MIG 323C



Features:

- Latest IGBT Multi Process Inverter Power Source
- Digital Volt / Amp Display
- Seamless Electronic Adjustment
- 4 Roll Wire Feed System
- Suitable for 0.6, 0.8 & 1.0mm Wire
- Will Accept 5 or 15 Kilogram Reel's
- VRD Safety Device
- Trolley Mounted
- Generator Friendly
- Easy Set Up & Operation

Functions:

- MIG/MAG
- MMA
- Burn Back Adjustment
- Wire Inching
- 2T/4T
- Gas Purge Function
- Variable Inductance

Package includes:

- 323C Inverter Power Source
- M2-4 Mtr MIG Welding Torch
- Earth Return Lead & Clamp
- Gas Hose
- 3 Mtr MMA Lead



TECHNICAL SPECIFICATIONS	
Input Voltage	3P-400 (+ - 15%) 50/60Hz
Input Current	20 (A)
Current Range MIG	40-300 (A)
Current Range MMA	25-300 (A)
Voltage Adjustment Range (v)	15-32
Duty Cycle @ 40°C	300A @ 60%
Wire Speed (m/min)	2-20
Efficiency (%)	85
Power Factor @ 100%	0.93
Protection / Insulation Class	IP21/F
Dimensions (mm)	935 x 445 x 810
Weight (Kg)	58
Conforms to	EN IEC 60974-10:2021 EN IEC 60974-1:2022
Approvals	CE UK CA

*See warranty form for terms and conditions